MOTOR SPEED PRODUCT LINE


SERIES: 4197

STAINLESS STEEL CONSTRUCTION

FEATURES & BENEFITS

- For corrosion resistance over a wider pH range
- Non-galling gear materials standard for handling thin liquid applications
- Compact gear pump series to fit tight space constraints













TEMPERATURE 0°F to +350°F (-20°C to +175°C)



VISCOSITY 28 to 25,000 SSU (1 to 5,500 cSt)








PERFORMANCE

MODEL	S	SPECIFICATIONS				
Foot Mou	nt	Perforr	nance	Standard Ports		
Mechanical	Seal Max	Speed, RPM	GPM	m³/h	Size, Inches	Туре
GG4197	'	1750	10	2.3	1	Flange
HJ4197		1750	20	4.5	1.5	Flange
HL4197		1750	30	6.8	1.5	Flange
AS4197		1150	35	8	3	Flange
AK4197	'	1150	50	11	3	Flange
AL4197		1150	75	17	3	Flange

CURVES



PORTING

- Opposite (180°)
- Flanged (ANSI)

SEALING

- · Behind the Rotor Seal
- · Balanced Seal

MOUNTING

Foot Mount

DRIVES





TYPICAL APPLICATIONS

- Fuels
- · Lube Oils

· Compressor Lubrication

VIKING PUMP°

VIKING PUMP, INC.

A Unit of IDEX Corporation 406 State Street Cedar Falls, Iowa 50613 U.S.A.

vikingpump.com

United States

Cedar Falls, Iowa Phone: (319) 266-1741

Canada vikingpumpcanada.com

Windsor, Ontario Phone: (519) 256-5438

Europe & Africa vikingpump.com

Asia-Pacific idexfmt-asia.com India - Mumbai Phone: +91-22-6643-5563

China - Shanghai Phone: +86-21-5241-5599 **Singapore** Phone: +65-6684-7305

Middle East

Dubai, UAE Phone: +971 4 2600300

Contact Your Stocking Distributor Today Distributed By:

Latin America

Australia & New Zealand

